Chapter 6: Nameless Representation of Terms

Terms and Contexts

Shifting and Substitution

Bound Variables

- Recall: bound variables can be renamed, at any moment, to enable substitution:

$$
\begin{array}{lcll}
[x \mapsto s]x & = & s & \\
[x \mapsto s]y & = & y & \text{if } y \neq x \\
[x \mapsto s](\lambda y.t_1) & = & \lambda y.\ [x \mapsto s]t_1 & \text{if } y \neq x \text{ and } y \notin FV(s) \\
[x \mapsto s](t_1\ t_2) & = & [x \mapsto s]t_1\ [x \mapsto s]t_2 &
\end{array}
$$

- Variable Representation
  - Represent variables symbolically, with variable renaming mechanism
  - Represent variables symbolically, with bound variables are all different
  - “Canonically” represent variables in a way such that renaming is unnecessary
  - No use of variables: combinatory logic

Terms and Contexts

Nameless Terms

- **De Bruijin** Idea: Replacing named variables by natural numbers, where the number k stands for "the variable bound by the k'th enclosing λ".
  - Examples:

λx.x	λ.0
λx.λy. x (y x)	λ.λ. 1 (0 1).

- **Definition** [Terms]: Let T be the smallest family of sets $\{T_0, T_1, T_2, \ldots\}$ such that

1. $k \in T_n$ whenever $0 \le k < n$;
2. if $t_1 \in T_n$ and $n>0$, then $\lambda.t_1 \in T_{n-1}$;
3. if $t_1 \in T_n$ and $t_2 \in T_n$, then $(t_1\ t_2) \in T_n$.

Note: T_n are set of terms with at most n free variables

Name Context

- Naming Context
  - To deal with terms containing free variables
  - $\Gamma = x \rightarrow 4;\ y \rightarrow 3;\ z \rightarrow 2;\ a \rightarrow 1;\ b \rightarrow 0$

- Examples

  Under the naming context Γ, we have

  - $x\ (y\ z)$ — $4\ (3\ 2)$
  - $\lambda w.\ y\ w$ — $\lambda.\ 4\ 0$
  - $\lambda w. \lambda a. x$ — $\lambda . \lambda . 6$

Shifting and Subtitution

How to define substitution $[k \rightarrow s]t$?

Shifting

- Under the naming context x → 1, z → 2

  [1 → 2 (λ.0)] λ.2 ➔ ?

  i.e., [x → z (λw.w)] λy.x ➔ ?

Definition [Shifting]: The d-place shift of a term $\mathtt{t}$ above cutoff c, written $\uparrow^d_c(\mathtt{t})$, is defined as follows:

$$
\begin{aligned}
\uparrow^d_c(\mathtt{k}) &= \begin{cases} \mathtt{k} & \text{if } k < c \\ \mathtt{k} + d & \text{if } k \geq c \end{cases} \\
\uparrow^d_c(\lambda.\mathtt{t}_1) &= \lambda.\ \uparrow^d_{c+1}(\mathtt{t}_1) \\
\uparrow^d_c(\mathtt{t}_1\ \mathtt{t}_2) &= \uparrow^d_c(\mathtt{t}_1)\ \uparrow^d_c(\mathtt{t}_2)
\end{aligned}
$$

We write $\uparrow^d(\mathtt{t})$ for $\uparrow^d_0(\mathtt{t})$. □

1. What is $\uparrow^2(\lambda.\lambda.\ 1\ (0\ 2))$?
2. What is $\uparrow^2(\lambda.\ 0\ 1\ (\lambda.\ 0\ 1\ 2))$?

Substitution

- Definition

$$[j \mapsto s]k = \begin{cases} s & \text{if } k = j \\ k & \text{otherwise} \end{cases}$$

$$[j \mapsto s](\lambda.t_1) = \lambda.\, [j+1 \mapsto \uparrow^1(s)]t_1$$

$$[j \mapsto s](t_1\ t_2) = ([j \mapsto s]t_1\ [j \mapsto s]t_2)$$

- Example

  [1 → 2 (λ.0)] λ.2 ➔ λ.3 (λ.0)

  i.e., [x → z (λw.w)] λy.x ➔ λy. z (λw.w)

Evaluation

$$(\lambda x.\ t_{12})\ t_2 \longrightarrow [x \mapsto t_2]t_{12},$$

How to change the above rule for nameless representation?

Evaluation

$$(\lambda x.\, t_{12})\ t_2 \longrightarrow [x \mapsto t_2]t_{12},$$

$$\Downarrow$$

$$(\lambda.t_{12})\ v_2 \quad \longrightarrow \quad \uparrow^{-1}([0 \mapsto \uparrow^{1}(v_2)]t_{12})$$

Example:

$$(\lambda.1\ 0\ 2)\ (\lambda.0) \longrightarrow 0\ (\lambda.0)\ 1$$

Homework

- Read Chapter 6.
- Do Exercise 6.2.5.

6.2.5 EXERCISE [★]: Convert the following uses of substitution to nameless form, assuming the global context is Γ = a,b, and calculate their results using the above definition. Do the answers correspond to the original definition of substitution on ordinary terms from §5.3?

1. $[\mathtt{b} \mapsto \mathtt{a}]\ (\mathtt{b}\ (\lambda\mathtt{x}.\lambda\mathtt{y}.\mathtt{b}))$
2. $[\mathtt{b} \mapsto \mathtt{a}\ (\lambda\mathtt{z}.\mathtt{a})]\ (\mathtt{b}\ (\lambda\mathtt{x}.\mathtt{b}))$
3. $[\mathtt{b} \mapsto \mathtt{a}]\ (\lambda\mathtt{b}.\ \mathtt{b}\ \mathtt{a})$
4. $[\mathtt{b} \mapsto \mathtt{a}]\ (\lambda\mathtt{a}.\ \mathtt{b}\ \mathtt{a})$ □